

## TITAN FLOW | TFW-100

High tack satin white print vinyl with micro channel liner developed for long term applications on powervehicles.

### FACE FILM

Polymeric PVC, satin white

Thickness (µm)	100	
Elongation at break (%)	>200	DIN EN ISO 527

### ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	30	
24 hours (180°) N/25mm	35	

### RELEASE LINER

Structured lay-flat kraft paper liner, double-sided PE-coated

Weight (gsm)	140	
--------------	-----	--

### PRODUCT APPLICATION

Dimensional stability (.mm)	<1,2	FINAT FTM 14
Application temperature (°C)	10 to 25	
Service temperature (°C)	-20 to 80	

### DURABILITY

Outdoor durability (years)	5	Northern-EU climate, vertical exposure
----------------------------	---	--

### ROLL SIZES

1370mm x 50m

### PRINTING METHOD

(Eco)-Solvent, Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in TITAN material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.