HP Latex 630 Printer



Embrace new possibilities with outstanding quality—easily



POSSIBILITIES—Level up your offering

- Produce a wide range of signage and décor jobs including applications with thin film and papers.
- Deliver stunning prints with vivid colours, smooth gradients, and sharp text at 14 m²/hr.¹
- Simple finishing, lamination, and installation with flexible inks and prints that come out dry.

EFFORTLESS—Get it done quickly and easily

- Find peace of mind with automatic maintenance processes and user-replaceable printheads.
- Save space and time with fast and automated frontloading system.
- Easily reprint projects with job storage in the printer up to 10 GB.
- Monitor your printer from anywhere and expand your capabilities with the cloud-based HP PrintOS app.

GO BEYOND—Lead with environmental certifications²

- Contribute to a comfortable³ working environment with water-based HP Latex Ink
- Differentiate your business with environmental certifications²—including UL ECOLOGO®4 and
- Reduce your plastics consumption with cartonbased cartridge⁶ and labelless supplies; free recycling via HP Planet Partners.

For more information, please visit https://www.hp.com/go/latex-600-series

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://lkc.hp.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ Standard mode (Generic SAV Calendar) 6-pass, 6 colours, 110% ink density. Based on internal HP testing on MACTAC JT 8500 WG-PG. Print speed may vary due to the adaptive printing mechanism, which is designed to

Eased on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at http://hp.com/go/latex

Based on odor sensory evaluation when printing with the HP Latex 600 series printer and Mimaki UJV 100-160. Tests done in a 57 sqm room with 5ACH. Test conducted by Odournet following the standard VDI3882,

where the HP Latex 600 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UIC 100-160.

4 UL ECOLOGO® Certified HP 832 Latex inks meet a range of stringent human health and environmental considerations. For certifications, see http://www.ul.com/EL and http://www.ul.com/gg

⁵ Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See http://epeat.net for registration status by country.

⁶ Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.

Visit http://hp.com/recycle to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposa

Technical specifications

18 m/hr - Speed (4-pass) 1 m/hr - Cuality (9-pass) 1 m/hr - Cuality (9	Print	
ink types Water-based HP Latex Inits ink carridges 8 Bladick, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat) Carridge size 1 L 5 C cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat) Song-term print-to-print specialishiny 8 Sol f colors < 3 dE20002 Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, fibrics, mesh, textilies, and any other porous materials require a lined 8 dead types 8 Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, fibrics, mesh, textilies, and any other porous materials require a lined 8 destruction of the porous materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 8 destruction of the process materials require a lined 9 destruction of the process	Printing modes	18 m²/hr - Speed (4-pass) 14 m²/hr - Standard (6-pass) 11 m²/hr - Quality (8-pass) 8 m²/hr - High Saturation (12-pass)
B (Budack, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat) 2	Print resolution	Up to 1200 x 1200 dpi
Servindge size 1.	Ink types	Water-based HP Latex Inks
S (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat) perpetability Media Anading Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas ² , paper-based media, and filing Relating Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas ² , paper-based media, and filing Relating types Banners, self-adhesie vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a line) Maximum roll weight 42 kg 437 to 1625-mm rolls (580 to 1625-mm rolls with full support) Maximum roll diameter 250 mm Thickness Up to 0.5 mm Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoo posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decats, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-1) Dimensions (W × D × H) Printer 2603 × 844 × 1405 mm 2603 × 1330 × 1271 mm Diperating area 2793 × 2100 mm Weight What's in the box Holtang of the Control of the Contro	Ink cartridges	8 (black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer, HP Latex Overcoat)
Media Media Media Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas", paper-based media, and filin develai types Banners, self-adhesive vinyls, films, papers, vallcoverings, canvas, synthetics, (flabrics, mesh, textiles, and any other porous materials require a liner) Roll size 457 to 1625-mm rolls (580 to 1625-mm rolls with full support) Maximum roll diameter 250 mm Thickness Up to 0.5 mm Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor porters, interior decoration, Labels and strickers, Light boxes - film, Light boxes - paper, PDP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity metricaes Gigabit Ethernet (1000Base-17) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Diperating area 2793 x 2100 mm Weight What's in the box What's in the box Applications 15 to 30°C 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dBA) (operating), 3.5 BIA) (dde), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 6.0 W (ready), <15 W (sleep) Input voltage (autor ranging) 200-240 V (± 10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords, 5 A max printer power cord, 12 A max curing power cord 165 (62368-1 2nd and 3rd ed and BC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (UVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Certification Letteromagnetic Compliant with Class A requirements, including; USA (FCC rules), Canada (CSS), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCC), Korea (RCC), China (CCC) Environmental ENGROY STAPP, ROMS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Cartridge size	1L
Media Roll feed, take-up real, automatic horizontal cutter (for vinyl, banner and canvas ² , paper-based media, and filin feed types Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a line?) Notifications 457 to 1625-mm rolls (580 to 1625-mm rolls with full support) Adaminum roll weight 42 kg Adaminum roll diameter 250 mm Thickiness Up to 0.5 mm Applications Banners, Customizable cothing, Displays, Exhibition and event graphics, Extenior signage, Floor graphics, Indoe posters, Interior decoration, Labels and stickers, Light boxes – film, Light boxes – paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-1) Dimensions (W x D x H) Printer 260 x 844 x 1405 mm Diperating area 2793 x 2100 mm Weight Printer 230 kg 347 kg What's in the box Applications, guick-reference guide, HP FlexiPRINT Basic Edition RIR documentation software, power cords, air puriets, can spindle adaptor Environmental ranges Diperating temperature 15 to 30°C Deperating hermidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dBA) (operating), 35 dBA) (dde), <20 dBIA) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Flower Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Flower Consumption 15 to 30°C Deperating hermidity 25 to 80°C (2368-1 2nd and 3rd et all all CC 60950-1+A1+A2 compliant; USA and Canada (CSA listed), EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Environmental ENERGY STAPP, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH; EPEAT; OSHA; CE marking compliant Environmental ENERGY STAPP, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey), REACH; EPEAT; OSHA; CE marking compliant	Printheads	5 (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Anadiling Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas³, paper-based media, and flinded types Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner) All size 457 to 1625-mm rolls (580 to 1625-mm rolls with full support) Adaminum roll weight 42 kg Adaminum roll diameter 250 mm Thickness Up to 0.5 mm Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoe posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (10008ase-T) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diparating area 2793 x 2100 mm Weight What's in the box HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP Fleo/PRINT Basic Edition RIP, documentation software, power cords, air purgers. 2-in spindle adaptor Environmental ranges Diparating temperature 15 to 30°C Diparating temperature 15 to 30°C Diparating temperature 55 dBIAN (operating), 38 dBIAN (idle), <20 dBIAN (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 w (ready), <15 W (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 w (ready), <15 W (sleep) Input voltage (auto ranging) 2200-240 V (<1094) two wires and PE; 50/60 Hz (<13 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Eaclery Ecception (ECG, 2668-1 2nd and 3rd ed and 16 C 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Chian (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (CES), EU (EMC Directive), Australia an New Zesland (RCN), Japan (VCC), Korea (KCC), China (CCC) Environmental E	Long-term print-to-print repeatability	95% of colors < 3 dE2000 ²
Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner) 457 to 1625-mm rolls (580 to 1625-mm rolls with full support) 42 kg 43 maintain roll diameter 250 mm Thickness Up to 0.5 mm Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-T) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diporating area 2793 x 2100 mm Weight What's in the box HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers. 2-in spendie adaptor Environmental ranges Diporating temperature 15 to 30°C Diporating temperature 15 to 30°C Diporating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dBIAN (operating), 35 BIAN (idele, < 20 dBIAN) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 w (ready), < 15 W (sleep) Power Certification Life C62368-1 2nd and 3rd ed and LEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EWC Directive), Australia an New Zealand (RCN), Japan (VCC), Korea (KCC), China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EWC Directive), Australia an New Zealand (RCN), Japan (VCC), Korea (KCC), China (CCC)	Media	
cother porous materials require a liner) Actol size 457 to 1625-mm rolls (580 to 1625-mm rolls with full support) Adaximum roll weight 42 kg Maximum roll diameter 250 mm Thickness Up to 0.5 mm Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, interior decreation, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, vehicle graphics, Well decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-T) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Decrating area 2793 x 2100 mm Weight What's in the box Holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purpers, 2-in spindle adaptor Environmental ranges Diperating temperature 15 to 30°C 20parating humidity 20 to 80% RH (non-condensing) Acoustics Sound power 7.5 B(A) (operating), 35 B(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 w (ready), <15 W (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 w (ready), <15 W (sleep) Foreigneents Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 54 max printer power cord; 12 A max curing power cord Certification Environmental Enropes (ECG, 25 EAC, 25	Handling	Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas ³ , paper-based media, and film)
Maximum roll weight 42 kg Maximum roll diameter 250 mm Thickness Up to 0.5 mm Applications Banners, Customizable lothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoo posters, Interior decoration, Labels and Stickers, Light boxes - Flim, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-IT) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diperating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box HD Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP ResiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Diperating humidity 20 to 80% RH (non-condensing) Acoustics Sound priessure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Eactive Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealard (RCM), Japan (VCC), Koree (VCC), China (CCC) Environmental Compliant: Compliant: USA RACH, EPEAT; OSHA; CE marking compliant:	Media types	
Applications Up to 0.5 mm Applications Up to 0.5 mm Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoposters, Interior decoration, Labels and stickers, Light boxes – film, Light boxes – paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-T) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Deparating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box Holtare Sid Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Deparating temperature 15 to 30°C Diperating temperature 15 to 30°C Diperating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE, 50/60 Hz (±3 Hz); two power cords; 54 max printer power cord; 12 A max curing power cord Certification Eactor Starker, RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant: Performental Certification Environmental Certification Performental Certification Environmental Certification Environmen	Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Applications	Maximum roll weight	42 kg
Applications Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-T) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diperating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Depreting temperature 15 to 30°C Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Fertification Gafety IEC 62369-1 2nd and 3rd ed and IEC 60950-1 +A1+A2 compliant; USA and Canada (CSA listed); EU (UVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Certification Environmental ENERGY STAR®, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Maximum roll diameter	250 mm
posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics Connectivity Interfaces Gigabit Ethernet (1000Base-T) Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diperating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box H Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP RexIPRINT Basic Edition RiP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Diperating temperature 15 to 30°C Diperating hunidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Input voltage (autor anging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Gafety General RCM), Japan (VCCI), Korea (KCC), China (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (CCS), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENKROY STAR®, ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Thickness	Up to 0.5 mm
Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diperating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Diperating temperature 15 to 30°C Diperating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety EC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant; USA and Canada (ICSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (ICCC) Environmental EN ERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant;	Applications	
Dimensions (W x D x H) Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Diperating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box H Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIR, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Diperating temperature 15 to 30°C Diperating temperature 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCC), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Connectivity	
Printer 2603 x 844 x 1405 mm Shipping 2800 x 1130 x 1271 mm Deparating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box Huatex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Deparating temperature 15 to 30°C Operating temperature 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCC), Korea (RCC), China (CCC) Environmental ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Interfaces	Gigabit Ethernet (1000Base-T)
Shipping 2800 x 1130 x 1271 mm Deprating area 2793 x 2100 mm Weight Printer 230 kg Shipping 347 kg What's in the box holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Deprating temperature 15 to 30°C Deprating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Foound power 7.5 B(A) (operating), 5.5 B(A) (idle), <40 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCO), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Dimensions (W x D	×H)
Weight Printer 230 kg Shipping 347 kg What's in the box holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Derating temperature 15 to 30°C Deparating temperature 15 to 30°C Deparating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Fower Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCO), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Printer	2603 x 844 x 1405 mm
Weight Printer 230 kg 347 kg What's in the box HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Derating temperature 15 to 30°C Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Found power 7.5 B(A) (operating), 5.5 B(A) (idle), <40 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Shipping	2800 x 1130 x 1271 mm
Printer 230 kg Shipping 347 kg What's in the box HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Operating temperature 15 to 30°C Operating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Found power 7.5 B(A) (operating), 5.5 B(A) (idle), <40 dB(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EM 62368-1 compliant); inclinding: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCO), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Operating area	2793 x 2100 mm
Shipping 347 kg What's in the box	Weight	
What's in the box HP Latex 630 Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edg holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Derating temperature 15 to 30°C Derating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) Sound power 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Printer	230 kg
holders, quick reference guide, HP FlexiPRINT Basic Edition RIP, documentation software, power cords, air purgers, 2-in spindle adaptor Environmental ranges Derating temperature 15 to 30°C Derating humidity 20 to 80% RH (non-condensing) Acoustics Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Shipping	347 kg
Deparating temperature 20 to 80% RH (non-condensing) ACOUSTICS Sound pressure 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCO), Korea (KCC), China (CCC) Environmental ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	What's in the box	
Operating humidity 20 to 80% RH (non-condensing) Acoustics 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (IVCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Environmental ran	ges
Acoustics 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (IVCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Operating temperature	15 to 30℃
55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep) 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep) Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord, 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (IVCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Operating humidity	20 to 80% RH (non-condensing)
Power O.9-2.0 kW (2.9 kW peak) (printing), 6.0 W (ready), <15 W (sleep) Input voltage (auto ranging) 200-240 V (± 10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Energy 1EC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Acoustics	
Power Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Sound pressure	55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Consumption 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep) Requirements Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Clectromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Sound power	7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)
Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord Certification IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Power	
printer power cord; 12 Å max curing power cord Certification Safety IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Consumption	0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep)
IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord
60950-1 and EN 62368-1 compliant); China (CCC) Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Certification	
Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia an New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC) Environmental ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant	Safety	IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC)
compliant	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and
Alarmantu One year liesited hardware warrantu	Environmental	ENERGY STAR®; ROHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant
warranty one-year umited nardware warranty	Warranty	One-year limited hardware warranty

Ordering information

Product

1715ZA	HP Latex 630 Printer
Accessories	
171K8A	HP Latex 600 Output Platen Protector Accessory
21V10A	HP Latex 700/800 User Maintenance Kit
421S3A	HP Latex Media Feed Accessory
7HR19A	HP Latex 700/800 Media Loading Accessory
171K8A 21V10A 421S3A	HP Latex 700/800 User Maintenance Kit HP Latex Media Feed Accessory

Original HP printing supplies

4UU94A	HP 836 Optimizer Latex Printhead	
4UV75A	HP 832 1-liter Black Latex Ink Cartridge	
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge	
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge	
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge	
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge	
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge	
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge	
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge	
4UV95A	HP 836 Black/Cyan Latex Printhead	
4UV96A	HP 836 Magenta/Yellow Latex Printhead	
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead	
4UV98A	HP 836 Overcoat Latex Printhead	
4UV99A	HP Latex Maintenance Cartridge	

Original HP large format printing materials

HP Recycled⁴ Removable Adhesive Fabric, 3-in Core (Latex/solvent): REACH compliant⁵
HP Recycled⁶ Satin Canvas, 3-in Core (Latex/solvent): REACH compliant⁵
HP Premium Poster Paper: FSC⁶ certified⁷
HP PVC-free⁸ Wall Paper: UL GREENGUARD GOLD Certified⁹, FSC⁶ certified⁷, meets AgBB criteria¹⁰ HP Permanent Gloss Adhesive Vinyl: REACH compliant⁵ HP Prime Gloss Air GP: REACH compliant⁵

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U60QHE HP 2 year Plus Service Plan Hardware Support w/DMR U60QJE HP 3 year Plus Service Plan Hardware Support w/DMR U60QLE HP 5 year Plus Service Plan Hardware Support w/DMR U600MPE HP 1 year Post Warranty Plus Service Plan Hardware Support w/DMR U600NPE HP 2 year Post Warranty Plus Service Plan Hardware Support w/DMR

Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects. Print mode names may vary depending on the media or application.
The color variation between printed jobs has been measured at 6 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard DEDE2000 as per CIE Draft Standard D5 014-6/E-2012. 5% of colors may experience variations above 3 dE2000. Backlit substrates measured in transmission mode may yield different results.

Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.
Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.

So the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization totherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.

evaluation-of-building

determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.

6 25% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin. Certified according to Global Recycled Standard (GRS) Version 3.0, March 2017.

7 Trademark license code FSC-C115319.

8 Chemical analysis demonstrated elemental chlorine to be below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.

9 HP PVC-free Wall Paper printed with HP Latex lisk is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://lu.com/gg

10 With HP Latex lisks, prints meet ApgBb criteria for health-related evaluation of VOC emissions. See http://unweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building

















