



HP Latex 630 W Print and Cut Plus Solution

Embrace new possibilities with unbeatable white ink printing¹ and a seamless print and cut workflow



POSSIBILITIES—The best white ink print experience¹

- Do more in your shop with the easiest white ink printer¹ that adapts to your business needs.
- Produce a wide range of signage and décor jobs including applications with thin film and papers.
- Deliver stunning prints with vivid colours, smooth gradients, and sharp text at 14 m²/hr.²
- Print and cut simultaneously with reliable dual-device solution—accurate job recognition, error-free cutting.

EFFORTLESS—Get it done quickly and easily

- Find peace of mind with automatic maintenance processes and user-replaceable printheads.
- Save space and time with fast and automated frontloading system.
- Easily reprint projects with job storage in the printer up to 10 GB.
- Monitor your printer from anywhere and expand your capabilities with the cloud-based HP PrintOS app.

GO BEYOND—Lead with environmental certifications³

- Contribute to a comfortable⁴ working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications³—including UL ECOLOGO^{®5} and EPEAT⁶.
- Reduce your plastics consumption with carton-based cartridge⁷ and labelless supplies; free recycling via HP Planet Partners.⁸

For more information, please visit <https://www.hp.com/go/latex-600-series>

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at <https://kc.hp.com/>

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

¹ Easiest/best white ink experience due to transparent ink maintenance with Automatic Ink Recirculation System between the HP Latex 832 Ink Mix and HP 832 White Latex Ink Cartridge. This ensures white ink is constantly circulating and doesn't settle. It's easy to remove the white printhead from the carriage and store it in an offline rotation chamber when not printing with white ink. This avoids unnecessary white ink waste and prevents the white printhead from getting clogged because of its dense white ink chemistry. All white printmodes are available at different white ink densities to get different levels of opacity (spot, underflood, overflood, and 3-layer—up to 260% white ink density).

² Standard mode (Generic SAV Calendar) 6-pass, 6 colours, 110% ink density. Based on internal HP testing on MACTAC JT 8500 WG-PG. Print speed may vary due to the adaptive printing mechanism, which is designed to avoid image quality defects.

³ Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at <http://hp.com/go/latex>

⁴ Based on odor sensory evaluation when printing with the HP Latex 600 series printer and Mimaki UJV 100-160. Tests done in a 57 sqm room with 5ACH. Test conducted by Odournet following the standard VDI3882, where the HP Latex 600 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UJC 100-160.

⁵ UL ECOLOGO[®] Certified HP 832 Latex inks meet a range of stringent human health and environmental considerations. For certifications, see <http://www.ul.com/EL> and <http://www.ul.com/gg>

⁶ Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See <http://epeat.net> for registration status by country.

⁷ Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.

⁸ Visit <http://hp.com/recycle> to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

Technical specifications

Print

Printing modes	35 m ² /hr - Max Speed (2-pass) 18 m ² /hr - Speed (4-pass) 14 m ² /hr - Standard (6-pass) 11 m ² /hr - Quality (8-pass) 8 m ² /hr - High Saturation (12-pass) 7 m ² /hr - Standard for Backlights and Textiles (14-pass) 6 m ² /hr - White Spot (100%) 3 m ² /hr - White Overflood (100%) 2 m ² /hr - White Underflood (100%) 1 m ² /hr - 3 Layers (160%) ¹
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	1 L
Printheads	6 (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print repeatability	95% of colors < 3 dE2000 ²

Media

Handling	Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas ³ , paper-based media, and film)
Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner)
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Maximum roll weight	42 kg
Maximum roll diameter	250 mm
Thickness	Up to 0.5 mm

Applications

Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics

Connectivity

Interfaces	Printer: Gigabit Ethernet (1000Base-T); Cutter: USB and Ethernet (LAN)
------------	--

Dimensions (W x D x H)

Printer	Printer: 2603 x 844 x 1405 mm; Cutter: 1960 x 704 x 1112 mm
Shipping	Printer: 2800 x 1130 x 1271 mm; Cutter: 2230 x 420 x 710 mm

Weight

Printer	Printer: 236 kg; Cutter: 48 kg
Shipping	Printer: 353 kg; Cutter: 74 kg

What's in the box

Printer: HP Latex 630 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP FlexiPRINT and CUT RIP, documentation software, power cords, air purgers, 2-in spindle adaptor; Cutter: HP Latex 64 Plus Cutter, cutter stand, media basket, HP Cutter Control software, quick reference guide, setup poster, documentation software, power cords, standard holder (1), standard blades (2), cut-off knife (1), 3-in media flanges (set of 2)

Environmental ranges

Operating temperature	15 to 30°C
Operating humidity	Printer: 20 to 80% RH (non-condensing); Cutter: 35 to 75% RH (non-condensing)

Acoustics

Sound pressure	Printer: 55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep); Cutter: 56 dB(A) (operating)
Sound power	Printer: 7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep); Cutter: <7.3 B(A) (operating)

Power

Consumption	Printer: 0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <15 W (sleep); Cutter: 34 W (working mode)
Requirements	Printer: input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord; 12 A max curing power cord; Cutter: 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); 2 A

Certification

Safety	IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC)
Electromagnetic	Printer: Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC); Cutter: Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC)
Environmental	Printer: ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant; Cutter: WEEE, RoHS (EU); CE marking compliant; REACH

Warranty

One-year limited hardware warranty

Cutting

Cut type	Drag-knife with TurboCut and Tangential emulsion modes
Cut width	158 cm
Cut speed	Up to 113 cm/sec diagonal
Acceleration	Up to 3 G diagonal
Accuracy	0.2% of movement or 0.25 mm, whichever is greater
Repeatability	±0.1 mm
Cut force	1 to 600 grams of downforce, in 5-gam steps
Cut thickness	0.05 to 0.25 mm; 0.6 mm with optional speciality blade

Ordering information

Product

171K7A	HP Latex 630 W Print and Cut Plus Solution
--------	--

Accessories

171K8A	HP Latex 600 Output Platen Protector Accessory
1UX44A	HP Latex Standard Blade Kit
1UX45A	HP Latex Specialty Blade Kit
21V10A	HP Latex 700/800 User Maintenance Kit
42153A	HP Latex Media Feed Accessory
7HR19A	HP Latex 700/800 Media Loading Accessory

Original HP printing supplies

4UJ93A	HP 836 White Latex Printhead
4UJ94A	HP 836 Optimizer Latex Printhead
4UV29A	HP 832 1-liter White Latex Ink Cartridge
4UV75A	HP 832 1-liter Black Latex Ink Cartridge
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge
4UV83A	HP 832 Ink Mix Container
4UV95A	HP 836 Black/Cyan Latex Printhead
4UV96A	HP 836 Magenta/Yellow Latex Printhead
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead
4UV98A	HP 836 Overcoat Latex Printhead
4UV99A	HP Latex Maintenance Cartridge

Original HP large format printing materials

HP Recycled⁴ Removable Adhesive Fabric, 3-in Core (Latex/solvent): REACH compliant⁵
 HP Recycled⁴ Satin Canvas, 3-in Core (Latex/solvent): REACH compliant⁵
 HP Premium Poster Paper: FSC[®] certified⁷
 HP PVC-free⁸ Wall Paper: UL GREENGUARD GOLD Certified⁹, FSC[®] certified⁷, meets AgBB criteria¹⁰
 HP Permanent Gloss Adhesive Vinyl: REACH compliant⁵
 HP Prime Gloss Air GP: REACH compliant⁵

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

U67G3E	HP 2 year Plus Service Plan Hardware Support w/DMR
U67G4E	HP 3 year Plus Service Plan Hardware Support w/DMR
U67G6E	HP 5 year Plus Service Plan Hardware Support w/DMR
U67G7PE	HP 1 year Post Warranty Plus Service Plan Hardware Support w/DMR
U67G8PE	HP 2 year Post Warranty Plus Service Plan Hardware Support w/DMR

¹ Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects. Print mode names may vary depending on the media or application.
² The color variation between printed jobs has been measured at 6 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 3 dE2000. Backlit substrates measured in transmission mode may yield different results.
³ Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.
⁴ Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.
⁵ As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.
⁶ 62% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin. Certified according to Global Recycled Standard (GRS) Version 3.0, March 2017.
⁷ Trademark license code FSC-C115319.
⁸ Chemical analysis demonstrated elemental chlorine to be below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.
⁹ HP PVC-free Wall Paper printed with HP Latex Inks is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://ul.com/gg>
¹⁰ With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See <http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building>

