

HP Latex 335 Print and Cut Solution

Expand—into wider applications with this 64-in true print and cut solution



Your perfect fit

- Do more apps—cut through stickers, customizable clothing, window graphics; reach indoor spaces solvent can't
- With HP Signage Suite in the box, no design skills are needed—bring your ideas to life in 3 simple steps¹
- Space is not the limit—HP print and cut uses essentially the same operating space as an integrated device²

True print and cut

- Print AND cut at the same time versus print OR cut with solvent—with this reliable, dual-device solution
- Avoid solvent wait time—prints come out dry, cut/laminate right away; no need to laminate short-term jobs³
- Print longer runs with reliable, highprecision cutting—high-accuracy Optical Positioning System (OPOS)

Reliable, integrated workflow

- Print and cut in 5 simple steps includes in-box HP FlexiPRINT and CUT RIP and friendly user interface
- One point workflow management edit/print jobs, including HP Barcode unattended cutting, without interruption
- Avoid the complexity of other dualdevices—the complete HP solution is designed to work as one

For more information, please visit hp.com/go/Latex335printandcut

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at hp.com/communities/LKC

¹ Requires an HP Applications Center account, Internet connection, and connected Internet-capable device. For more information, see hpapplicationscenter.com

- ² Based on operating area requirements, the HP dual-device print and cut solution requires less than 1 m² of additional space compared to integrated solvent-technology based print and cut solutions in the market as of February, 2017.
- ³ You can consider unlaminated use for short-term signage with scratch resistance comparable to hard-solvent inks on self-adhesive vinyl and PVC banner. Scratch-resistance comparison based on testing thirdgeneration HP Latex Inks and representative hard-solvent inks. Estimates by HP Image Permanence Lab on a range of media.

Technical specifications

HP Latex 335 Pr		F0 m2/by (F20 fk2/by) Dill
Printing	Printing modes	50 m²/hr (538 ft²/hr) - Billboard (2 pass)
		23 m²/hr (248 ft²/hr) - Outdoor High Speed (4 pass)
		17 m²/hr (183 ft²/hr) - Outdoor Plus (6 pass)
		13 m²/hr (140 ft²/hr) - Indoor Quality (8 pass)
		$\frac{10 \text{ m}^2/\text{hr} (108 \text{ ft}^2/\text{hr}) - \text{Indoor High Quality (10 pass)}}{6 \text{ m}^2/\text{hr} (65 \text{ ft}^2/\text{hr}) - \text{Backlits, Textiles, and Canvas (16 pass)}}$
		5 m²/hr (54 ft²/hr) - High Saturation Textiles (20 pass)
	Print resolution	Up to 1200 x 1200 dpi
	Margins	5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in)
	Ink types	HP Latex Inks
	Ink cartridges	Black, cyan, light cyan, light magenta, magenta, yellow, HP Latex Optimizer
	Cartridge size	775 ml
	Printheads	6 (2 cyan/black, 2 magenta/yellow, light cyan/light magenta, 1 HP Latex Optimizer)
	Color consistency ⁴	Average ≤ 1 dE2000, 95% of colors ≤ 2 dE2000
Media	Handling	Roll feed; take-up reel; automatic cutter (for vinyl, paper-based media, backlit polyester film)
	Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textile and any other porous materials require a liner)
	Roll size	254 to 1625-mm (10 to 64-in) rolls (580 to 1625-mm (23 to 64-in) rolls with full support)
	Roll weight	42 kg (92.6 lb)
	Roll diameter	250 mm (9.8 in)
	Thickness	Up to 0.5 mm (19.7 mil)
Applications	Exterior signage, Floo	e clothing, Displays, Exhibition and event graphics, r graphics, Indoor posters, Interior decoration, Labels es - film, Light boxes - paper, POP/POS, Posters, Vehicle Window graphics
Connectivity	-	Gigabit Ethernet (1000Base-T)
Dimensions	Printer	2561 x 840 x 1380 mm (101 x 33 x 54 in)
(w x d x h)		2795 x 760 x 1250 mm (110.1 x 30 x 49.3 in)
	Printer (Shipping)	
Weight	Printer Printer (Shipping)	208 kg (459 lb) 290 kg (639.5 lb)
What's in the box	HP Latex 335 Printer, take-up reel, variable	printheads, maintenance cartridge, printer stand, spindle, front tension kit, user maintenance kit, edge holders, , setup poster, power cords
Environmental		15 to 30°C (59 to 86°F)
ranges	temperature	· · · · · · · · · · · · · · · · · · ·
	Operating humidity	20 to 80% RH (non-condensing)
Acoustic	Sound pressure	55 dB(A) (printing); 39 dB(A) (ready); < 15 dB(A) (sleep)
	Sound power	7.4 B(A) (printing); 5.7 B(A) (ready); < 3.5 B(A) (sleep)
Power	Consumption Requirements	2.6 kW (printing); 72 watts (ready); < 2.5 watts (sleep) Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 3 A max per
		printer power cord; 16 A max per curing power cord
Certification	Safety	IEC 60950-1+A1+A2 compliant; USA and Canada (CSA listed); EU (LVD and EN 60950-1 compliant); Russia, Belarus, and Kazakhstan (EAC); Australia and New Zealand (RCM)C)
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI)
	Environmental	ENERGY STAR, WEEE, RoHS (EU, China, Korea, India, Ukraine, Turkey), REACH, EPEAT Bronze, OSHA, CE marking compliant
Warranty	One-year limited hard	ware warranty
HP Latex 64 Cut	ter	
Cutting	Cut type	Drag-knife with TurboCut and Tangential emulation modes
	Cut width	158 cm (62.2 in)
	Cut speed	Up to 113 cm/sec (44 in/sec) diagonal
	Acceleration	Up to 3 G diagonal
	Accuracy	0.2% of movement or 0.25 mm, (0.01 in) whichever is greater
	Repeatability	±0.1 mm (0.004 in)
	Cutforco	0 to 400 grams of downforco in 5 gram stops

Connectivity	Interfaces (standard)	USB and Ethernet (LAN)	
Dimensions	Cutter	1980 x 680 x 1145 mm (77.9 x 26.8 x 45.1 in)	
(w x d x h)	Cutter (Shipping)	2110 x 480 x 670 mm (83.1 x 18.9 x 26.4 in)	
Weight	Cutter	54 kg (119 lb)	
	Cutter (Shipping)	78 kg (172 lb)	
What's in the box	HP Latex 64 Cutter, cutter stand, HP FlexiPrint and Cut RIP, HP Cutter Control software, quick reference guide, setup poster, documentation software, power cords, standard holder (1), standard blades (2), cut-off knife (1), 3-in media flanges (set of 2)		
Warranty	One year, after the HP HP authorized reselle	Latex End of Installation Registration is completed by an r	

Ordering information

Product	1LH37A	HP Latex 335 Print and Cut Solution	
Accessories	1UP26A	HP Latex Cutter Extended Kit	
	1UP27A	HP Latex 2-in Media Holder Kit	
	1UX44A	HP Latex Standard Blade Kit	
	1UX45A	HP Latex Specialty Blade Kit	
	F0M56A	HP Latex 64-in Printer 2-in Spindle	
	F0M58A	HP Latex 64-in Printer 3-in Spindle	
	F0M59A	HP Latex 300/500 User Maintenance Kit	
Original HP printheads	CZ677A	HP 831 Cyan/Black Latex Printhead	
	CZ678A	HP 831 Yellow/Magenta Latex Printhead	
	CZ679A	HP 831 Light Magenta/Light Cyan Latex Printhead	
	CZ680A	HP 831 Latex Optimizer Printhead	
riginal HP ink	CZ694A	HP 831C 775-ml Black Latex Ink Cartridge	
artridges and	CZ695A	HP 831C 775-ml Cyan Latex Ink Cartridge	
naintenance	CZ696A	HP 831C 775-ml Magenta Latex Ink Cartridge	
upplies	CZ697A	HP 831C 775-ml Yellow Latex Ink Cartridge	
	CZ698A	HP 831C 775-ml Light Cyan Latex Ink Cartridge	
	CZ699A	HP 831C 775-ml Light Magenta Latex Ink Cartridge	
	CZ706A	HP 831 775-ml Latex Optimizer Ink Cartridge	
	CZ681A	HP 831 Latex Maintenance Cartridge	
)riginal HP arge format	HP printing materials are designed together with HP Latex Inks and HP Lat printers to provide optimal image guality, consistency, and reliability.		
rinting	HP Permanent Gloss Adhesive Vinyl REACH ⁵		
naterials	HP Backlit Polyester Film 🛟		
	HP PVC-free Durable Smooth Wall Paper REACH, ⁵ FSC [®] certified, ⁷ UL GREENGUARD GOLD Certified [®]		
	HP Premium Poster Paper () ⁶ FSC [®] certified ⁷		
	For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.		
Service and support	U9PN8E	HP 2 year Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support	
	U9PN9E	HP 3 year Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support	
	U9PP2PE	HP 1 year Post Warranty Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support	
	U9PP3PE	HP 2 year Post Warranty Next Business Day with Defective Media Retention Print&Cut Latex 335 HW Support	

 The color variation inside a printed job has been measured to be within this limit; maximum color difference (95% of colors) < 2 dE2000. Reflective measurements on a 943 color target under CIE standard Illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 2 dE2000. Backlit substrates measured in transmission mode may yield different results.

⁵ This product does not contain substances listed as SVHC (155) per Annex XIV of the EU REACH directive published as of June 16, 2014 in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Declaration published at <u>HP Printing Products and</u> <u>Consumable Supplies</u>.

⁶ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See <u>HPLFMedia.com/hp/ecosolutions</u> for details.

your area. See <u>HPLFMedia.com/hp/ecosolutions</u> for details. ⁷ BMG trademark license code FSC®-C115319, see <u>fsc.org</u>. HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions.

⁸ UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <u>ul.com/gg</u> or greenguard.org.



NOTE: Some certifications may only apply to the printer

© Copyright 2017 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

0 to 400 grams of downforce, in 5-gram steps

optional sandblast blade

0.05 to 0.25 mm (0.002 to 0.01 in); 0.8 mm (0.03 in) with



Cut force

Cut thickness